

Hipolava

REF:410.0127

Garanta a qualidade do seu trabalho com os produtos Sollac, respeitando as instruções de utilização dos nossos produtos.

DESCRIPTION

Product based on sodium hydroxide solution used for cleaning roofs.

PROPERTIES

- Easy to apply;
- Effective cleaning

USE

Recommended for removing all types of stains on surfaces contaminated by fungi and mold, such as roofs, facades and floors.

PREPARATION

Substrates must be clean, degreased, dry and free from loose particles, moisture and infiltrations.

APPLICATION

- Painting System: Sprayer;
- Product preparation:
 - Roofs - to remove stains, add 50 mL of Hipolava to 1 L of water. Apply the solution and let it act for 10 minutes, then scrub using the same solution and rinse with clean water;
 - Floor whitening - use a toothbrush soaked in a mixture of 1 part Hipolava and 5 parts water;
 - Wall whitening - simply apply a mixture of 1 part Hipolava and 5 parts water to the area in question, then rinse with a cloth dampened with clean water and let it dry.
- Application conditions:
 - Temperature - $\geq 5^{\circ}\text{C}$;
 - Relative humidity - $<70\%$;
 - Support temperature - $2/3^{\circ}\text{C}$ above the dew point temperature;
 - Do not paint with the support very hot from exposure to the sun;

Empresa Certificada:



Membro:



Cofinanciado por:



SOLLAC TINTAS

Newger Lda. - Estrada Nacional 8
Pavilhões FAS - Pav. B-09
Cruz do Barro - Torres Vedras
PORTUGAL

geral@sollac.pt
www.sollac.pt

Hipolava

REF:410.0127

Garanta a qualidade do seu trabalho com os produtos Sollac, respeitando as instruções de utilização dos nossos produtos.

PHYSICAL DESCRIPTION

- Color: Colorless;
- Surface drying time: 1 to 2 hours
- Deep drying time: 4 to 8 hours

YIELD

about 5-6 m² each litre

PACKAGING

1, 5 , 25 litres

HEALTH AND SAFETY

Avoid contact with eyes and skin, wear gloves, goggles and suitable clothing. Keep out of reach of children. Use only in areas with good ventilation. Do not dispose of waste in drains. Do not ingest. Keep the packaging tightly closed, in a safe place and in the correct position. Do not use or store under extreme temperature conditions. Sollac Quartz Primer does not cause skin or other irritation. It is recommended to apply in a ventilated environment and to wear gloves, a protective mask and appropriate clothing at the same time. The application material should be cleaned before it dries, using water. Do not dispose of residues down the drain. Keep out of reach of children. Keep the packaging tightly closed and in a suitable place. Do not use or store the product under extreme temperature conditions. For more information, see the product's Safety Data Sheet.

Notes:

This Technical Data Sheet cancels and replaces previous versions. The information provided is correct according to our tests, but is given without guarantee, since the conditions of application are beyond our control.

It is advisable to periodically consult the Technical Data Sheets for the products mentioned. Newger Lda. - Sollac Tintas, guarantees that its products comply with the specifications in the Technical Data Sheets. The technical advice provided by Newger Lda. - Sollac Tintas, before or after delivery of the products, is merely indicative, given in good faith and constitutes its best knowledge in accordance with current application techniques, and cannot in any case be held responsible for misapplication.

Complaints must be made in writing within 10 days of discovery and will only be accepted in respect of manufacturing defects or non-conformity with the order form. The sole obligation of Newger Lda. - Sollac Tintas shall be, respectively, to replace or refund the price already paid for the goods when it is recognised, and verified by our company's technicians, that there has indeed been a manufacturing defect or non-conformity with the order form, and shall not accept any other liability for any other loss or damage.

The VOC value indicated refers to the 'ready to use' product, including dilution. We disclaim any liability for mixing operations carried out with other commercial products of which we do not know the exact VOC content.

(a) The VOC value referred to above refers to the product ready for use, according to the technical characteristics recommended by us. We cannot be held responsible for other mixtures made with the product. We would like to draw the attention of all our agents to the responsibility they incur by not complying with Directive 2004/42/EC.

Empresa Certificada:



Membro:



Cofinanciado por:



SOLLAC TINTAS

Newger Lda. - Estrada Nacional 8
Pavilhões FAS - Pav. B-09
Cruz do Barro - Torres Vedras
PORTUGAL

geral@sollac.pt
www.sollac.pt